



アモルファスシリコン太陽電池 仕様

Model : AM-1819C

1. Outside dimensions 外形寸法

Light Receiving Side (受光面)

Overcoat Side (オーハークート面)



(dimension : mm)

Note

Glass Substrate Thickness (ガラス基板厚) : 1.1mm ± 0.1

Module Thickness (モジュール厚) : 1.3mm MAX

Accepts normal soldering for bending

(一般の半田を使用してリート線付けが可能です。)

2. Rated Specifications (at 25°C)

Item	Specifications (Initial)
2.1 Open circuit voltage : Voc 開放電圧	Typical 5.0V at 200Lx FL
2.2 Short circuit Current : Isc 短絡電流	Typical 8.1 μA at 200Lx FL
2.3 Operating Voltage & Operating Current : Vope - Iope 動作特性	Typical 2.6V - 1.6 μA at 50Lx FL
	Minimum 3.0V - 5.5 μA at 200Lx FL
	Typical 3.0V - 6.9 μA at 200Lx FL
2.5 Working temperature range : Topr 動作温度範囲	-10 to 60°C
2.6 Storage temperature range : Tstg 保存温度範囲	-20 to 70°C


FL : White Fluorescent Light

アモルファスシリコン太陽電池 仕様


Model : AM-1819CA

1. Outside dimensions 外形寸法

Light Receiving Side (受光面)



Overcoat Side (オーバーコート面)



(dimension : mm)

Lead Wires : AWG28	
a : 40	b : 40

Note
 Glass Substrate Thickness (ガラス基板厚) : 1.1mm ± 0.1
 Module Thickness (モジュール厚) : 1.3mm MAX
 Wire-Solder thickness : 2.5mm MAX (including Module)
 (リード線半田付け部厚)

2. Rated Specifications (at 25°C)

Item	Specifications (Initial)
2.1 Open circuit voltage : Voc 開放電圧	Typical 5.0V at 200Lx FL
2.2 Short circuit Current : Isc 短絡電流	Typical 8.1 μA at 200Lx FL
2.3 Operating Voltage & Operating Current : Vope - Iope 動作特性	Typical 2.6V - 1.6 μA at 50Lx FL
	Minimum 3.0V - 5.5 μA at 200Lx FL
	Typical 3.0V - 6.9 μA at 200Lx FL
2.5 Working temperature range : Topr 動作温度範囲	-10 to 60°C
2.6 Storage temperature range : Tstg 保存温度範囲	-20 to 70°C

FL : White Fluorescent Light


I - V Characteristics

REFERENCE

1.Model : AM-1819

2.Outside Dimension : 31.0mm × 24.0mm

FL:White Fluorescent Light



*このデータは標準的な出力特性を示すものであり、特性を保証するものではありません。

*The data are meant to show standard electric characteristics only , not intended to guarantee the characteristics.

Amorton

2026/2/27

出力の照度依存特性


REFERENCE

Dependence of Output on Illumination

1.Model : AM-1819

2.Outside Dimension : 31.0mm × 24.0mm

FL:White Fluorescent Light



*このデータは標準的な出力特性を示すものであり、特性を保証するものではありません。

*The data are meant to show standard electric characteristics only , not intended to guarantee the characteristics.

Amorton

出力の温度依存特性



REFERENCE

Dependence of Output on Temperature

1.Model : AM-1819

2.Outside Dimension : 31.0mm × 24.0mm

at 200Lx White Fluorescent Light



*このデータは標準的な出力特性を示すものであり、特性を保証するものではありません。

*The data are meant to show standard electric characteristics only , not intended to guarantee the characteristics.

Amorton

2026/2/27